## newline

All Stars

Elara is the eighth largest moon of Jupiter. And with a size of only 2% of Europe, the smallest of the four Galilean moons.



















## MOST POWERFUL ALLROUNDER

As the more powerful sister of Lyra, Elara really steals the show. This high-end interactive display carries every experience you could want in your workspace; faster, enhanced sound, a superior touch and writing experience due to optical bonding, a modular camera and built-in microphone making Elara a true hybrid solution. The extra wide viewing angle ensures everyone in the room can benefit from the crystalclear 4K image and vibrant colours. Elara has it all!



## **NEWLINE INTERACTIVE ECOSYSTEM**

The completely renewed Interactive Ecosystem is full of software that helps you use your interactive display to the max. Whether it's setting up your video conference super fast, using concept mapping to brainstorm, connecting your device, sharing your screen or broadcasting!

























Wifi & Bluetooth

100W Powered USB Type-C

Secure Multi **User Profiles** 







Broad Compatibility

High Quality Sound incl. Subwoofer

SDM-S Ready









MODEL Elara 65"	TT-6522Q	FRONT I/O USB Type-C (PD 100 W)	1
Elara 75"	TT-7522Q	HDMI IN 2.0	1
Elara 86"	TT-8622Q	USB Type-B (Touch)	1
Liara 00	11 00220	USB 3.0 Type-A	1
		Microphone In	1
DISPLAY		Microphone III	1
Backlight	Direct LED (Wide color gamut +	DEAD I/O	
	Anti blue light)	REAR I/O HDMI IN 2.0	2
Display Area	65" 4K: 1428 x 804 mm		1
	75" 4K: 1650 x 928 mm	DisplayPort 1.2	•
Disular Datis	86" 4K: 1895 x 1066 mm	USB Type-B (Touch) USB 3.0 Type-C (no PD)	1
Display Ratio Resolution	16:9	USB 3.0 Type-C (10 PD)	2
Colors	3840 x 2160 (4K)	USB 3.0 Type-A to Android	1
	1,07 Billion	HDMI OUT 2.0	1
Brightness Contrast Ratio	400 cd/m <sup>2</sup> 5000:1	RS232	1
		RJ45 (Gigabit)	IN x 1 & OUT x1
Response Time	6 ms	OPS Slot	1
Viewing Angle	H = 178, V = 178 typ. ≥50000 hours	SPDIF	1
Display Life Time	≥50000 nours		1
		Audio Line Out WIFI Module Slot	1
POWER CONSUMPTION	CEN 41/ 100 ) **	SDM-S Slot	1
Power Consumption (Eco mode)	65" 4K: 133 W		
	75" 4K: 150 W	Power Delivery connection (180W)	
Power Consumption	86" 4K: 168 W	(10077)	
(Standby mode)	<0,5 W	SMART SYSTEM	
(Standby friode)		SoC Chipset	Amlogic A311D2 octa-core
TOUCH TECHNOLOGY		300 Chipset	processor 4 x Cortex-A73 at
Touch Solution	IR		2,2Ghz, 4 x Corte x-A53 at 2,0Ghz
Glass Surface Technology	Anti-Glare+Anti-Fingerprint,	RAM	8 GB DR4
olass ourrace recrinology	+ Antimicrobial Tempered Glass	Storage	128 GB
Transparency	88%±3	Android Version	Android 11
Haze	2 %~5%	Multimedia File Formats Support	
Touch Surface Hardness	7H	For Image	SI EG, DIVII , I ING
Touch Points	32 Windows & 20 Android		MDEC1 MDEC2 MDEC4
Gap between Glass and OC	Certified Optical Bonding	Multimedia File Formats Support For Video	SorensonH.263,H.263,H.264,
Touch Screen Writing Tools	Stylus, Finger, Palm	1 of video	HEVC/H.265,MVC,AVS,A
Number of stylus	2		VS+,WMV3,VC1,Motion
Accuracy	±1 mm		JPEG,VP8,VP9,RV30/RV40
· · · · · · · · · · · · · · · · · · ·		Multimedia File Formats Support	
SPEAKER		For Audio	@LAYER3, EAC3, ACC-LC,
Speaker Position	Front		HEAAC, VORBIS, LPCM, IMA-
Speaker Rated Impedance	6 Ω		ADPCM,MS-ADPCM,G711 A/MU-
Speaker Freq.Response	250 Hz-20 KHz SPL -10 dB		LAW,LBR(COOK),FLAC
Output S.P.L.	77±2 dB	Drovimity Congor	2
Speaker Max.Power Output	20 W x 2	Proximity Sensor	
opeaker Max.r ower output	20 W X Z	Camera Slot	Included
CURWOOFFR		Wi-Fi 6	Included
SUBWOOFER On colour Decition	Deer	Bluetooth 5.0	Included
Speaker Position	Rear		
Speaker Rated Impedance	4Ω	CAMERA MODULE	
Speaker Freq.Response	20 Hz-20 KHz SPL -10 dB	Camera Resolution	4K@ 30 Hz /UHD
Output S.P.L.	77±2 dB	Field of View	120° FOV Lenses
Speaker Max.Power Output	15 W x 1	IR Camera	352 x 352 / 15 fps
		Camera Tile Range	15°
MICROPHONE	O Missonham - Association - 5		
Mic Possition	8 Microphone Array Upper Front	TRANSPORTATION / STORAGE	
Pick Up Distance	8 m	Outline Dimension	65" 4K: 1509 x 865 x 86 mm
Mic Performance	Echo cancellation, Beamforming,	(without wall mount bracket	75" 4K: 1731 x 1010 x 86 mm
	Noise Reduction	thickness)	86" 4K: 1977 x 1150 x 86 mm
		Net Weight	65" 4K: 36 Kg
			75" 4K: 49 Kg 86" 4K: 60 Kg
		VESA	65" 4K: 600 x 400 mm
		VLOM	75" 4K: 800 x 400 mm



## Newline-interactive.com/eu

75" 4K: 800 x 400 mm 86" 4K: 800 x 400 mm